

Bluetooth Serial Adapter,
Parani™ SD1100



Features


- Provides transparent RS422/485 serial cable replacement
- Bluetooth Specification v2.0 + EDR
- Supports up to 4 multiple simultaneous connections
- Basic Transmit Power: Max. +18dBm, EDR Transmit Power: Max. +6dBm
- Receiving Sensitivity: -88dBm(0.1%BER)
- Supports Bluetooth profiles SPP(Serial Port Profile)
- Interoperability with PDA, laptops etc.
- Supports firmware upgrade via windows-based software (ParaniUpdater)
- Working distance (In an open field): Nom. 100 meters, up to 1000m using patch antenna
- Easy to use Windows configuration tool available.
- No external drivers required.

The Parani-SD1100 is a Class1 type of Bluetooth Serial Adapter that supports 100 meters of wireless transmit distance by default. The Parani-SD1100 has an extension option so that users can extend the transmit distance up to 1000 meters using optional antennas. It supports Bluetooth v2.0+EDR specification. The Parani-SD1100 also supports up to 4 multiple simultaneous connections.

Typical application areas of the Parani-SD1100 include:

- RS422/485 Cable Replacement
- Truck/Bus Monitoring System
- Car Diagnostics
- Wireless POS System
- Wireless Machine(Healthcare/Industrial) Monitoring
- Wireless Factory Monitoring
- PLC Programming
- Wireless Printing
- Wireless Logistics

Panel Layout



Specifications

Serial Interface

- Serial speed up to 921.6kbps
- RS422: TXD+, TXD-, RXD+, RXD-
- RS485: TRXD+, TRXD-

Bluetooth Interface

- Bluetooth v2.0 + EDR
- Class 1
- Profiles - SPP
- Working distance (in open field)

SAT-G01R	-	SAT-G01R	100 meters
SAT-G01R	-	DAT-G01R	150 meters
DAT-G01R	-	DAT-G01R	200 meters
DAT-G01R	-	DAT5-G01R	300 meters
DAT-G01R	-	PAT-G01R	500 meters
DAT5-G01R	-	DAT5-G01R	400 meters
DAT5-G01R	-	PAT-G01R	600 meters
PAT-G01R	-	PAT-G01R	1,000 meters

[Antennas]

- SAT-G01R: +1dBi Stub Antenna
- DAT-G01R: +3dBi Dipole Antenna
- DAT5-G01R: +5dBi Dipole Antenna
- PAT-G01R: +9dBi Patch Antenna

Max. Tx power: +18dBm

Receive Sensitivity: -88dBm

Configuration

- ParaniWin, ParaniUpdater
- Modem AT command set

Diagnostic LED

- Power
- Standby
- Connect
- Serial-Tx
- Serial-Rx

Power

- Power input: 5~12VDC
- Power Consumption: Minimum 2mA, Maximum 80mA
- Common Power supply options
 - Power via a standard AC-plug DC-adapter
 - Power via USB power cable
 - Power via DC power cable
 - Power via Pin 1 and Pin 6 of DB Connector

Environmental

- Operating temperature: -20°C to 70°C
- Storage temperature: -40°C to 85°C
- Humidity: 90% Non-condensing

Physical properties

- Dimension (L x W x H)
 - 76 x 31 x 16 (mm)
- Weight
 - 24g

Certification

- FCC, CE, KCC, TELEC, SIG

Warranty

- 3-year limited warranty

Ordering Information

Single Pack SD1100-A1 Includes ✖ Stub antenna NOT included

- SD1100: SD1100 Bluetooth-serial adapter

Single Pack SD1100-00 Includes

- SD1100: SD1100 Bluetooth-serial adapter
- DPA-G01: Parani-DPA DC power cable for SD series
- UPA-G01: Parani-UPA USB Power Cable
- SAT-G01R: 1 dBi Stub Antenna - RP-SMA Plug Right-hand Thread
- DB9FTB-G01: DB9 Male to TerminalBlock Adapter

Single Pack SD1100-01 Includes

- Single pack SD1100-00
- OPA-G01: Parani-OPA External Power Adaptor - Includes one of four (EU, America, UK, Australia) regional power plugs
- DB9FTB-G01: DB9 Male to TerminalBlock Adapter

Bulk Pack SD1100-B10 Includes

- SD1100(×10EA): SD1100 Bluetooth-serial adapter
- SAT-G01R(×10EA): 1 dBi Stub Antenna - RP-SMA Plug Right-hand Thread
- DPA-G01(×10EA): Parani-DPA DC power cable for SD series

Optional Accessories

- SAT-G01R: 1 dBi Stub Antenna - RP-SMA Plug Right-hand Thread
- DPA-G01: Parani-DPA DC power cable for SD series
- UPA-G01: Parani-UPA USB Power Cable
- OPA-G01: Parani-OPA External Power Adaptor - Includes one of four (EU, America, UK, Australia) regional power plugs
- DAT-G01R: 3 dBi Dipole Antenna - RP-SMA Plug Right-hand Thread
- DAT5-G01R: 5 dBi Dipole Antenna - RP-SMA Plug Right-hand Thread
- PAT-G01R: 9dBi Patch Antenna with RP-SMA Plug Right hand Thread Default Cable.
(SMA Jack Right hand Thread w/o Default Cable)
- SEC-G01R: 15cm Extension Cable(For SAT-G01R / DAT-G01R / DAT5-G01R)
- RFC-G01R: 1m Extension Cable(For PAT-G01R)
- DB9FTB-G01: DB9 Male to TerminalBlock Adapter
- LTC100PC: LTC100PC RS232-RS422/485 converter for Parani-SD1100, port-powered, DC power supply optional

**For more information,
 please visit us at <http://www.sena.com>**

U.S. / Canada / South America

Tel: 408-448-1997 Fax: 408-907-3738
 Toll Free (US/Canada): 8668-US-SENA (866-887-7362)

EU / Africa

Tel: +33 (0)1 53 53 16 29 Fax: +33 (0)1 70 24 70 90

Asia / Pacific

Tel: +82-2-576-7362 Fax: +82-2-573-7710

Contact us via E-mail

General Information: info@sena.com
 Sales & Distribution: sales@sena.com
 Technical Support: support@sena.com